

# BBR 100

Blood bank refrigerator

## BBR SERIES

- Stainless steel interior
- Telescopic drawers
- White exterior
- Right hand hinged reversible door
- Automatic door closing and key lock
- Castors
- Air forced cooling
- Chart recorder



+ 4 °C

## ALL STANDARD FEATURES

- Micro processor controller with digital display
- Approx. 72 hours battery back up for alarms, loggings and temperature display in case of power cut
- Prepared for GSM alarm
- Prepared for connection of 2 additional probes
- Auto cycle in case of probe failure
- Ambient temperature display
- Direct download of logged data on USB memory stick
- Direct upload of new software via USB memory stick
- 3-level password protected
- Battery level indication
- Display text available in different languages
- Temperature graph
- Integrated data logger
- RS485/RS232 interface
- Integrated memory for 20 years
- Visual and acoustic alarm
- Adjustable high/low temperature alarm
- Power failure alarm
- Probe failure alarm
- Instrument failure alarm
- Open door alarm
- Contact for remote alarm
- Shows all alarms

→ Battery backup - 72 hours

→ Integrated data logger with memory

→ RS485/RS232 interface

→ On/off protection

The Arctiko BBR range is a perfect combination of unique temperature uniformity and reliable technology. Experience the BBR models with advanced controller, integrated non-manipulative data logger with USB read out and chart recorder as standard.

MODEL	BBR 100
Item code	DAI 0770
Dimensions exterior WxDxH (mm)	610x650x790
Capacity (L)	94
Temperature range (°C)	+4
Power supply (V)	230
Frequency (Hz)	50/60
Standard / max. no. of drawers	2/2
Standard / max. qty. of blood bags	72/72

# ARCTIKO

The art of simplicity®

# Technical specifications

Item code	DAI 0770
Dimensions exterior WxDxH (mm)	610x650x790
Capacity (L)	94
Dimensions interior WxDxH (mm)	490x440x434
Insulation (mm)	60
Temperature range (°C)	+4
Max. ambient temperature (°C)	25
Power supply (V)	230
Frequency (Hz)	50/60
Power consumption (KWH/24H)	2,2
Current (A)	1,4
Weight (KG)	71
Shipping weight (KG)	87
Shipping weight with wooden packaging (KG)	-
Shipping dimensions WxDxH (mm)	840x720x1010
Shipping dimensions with wooden packaging WxDxH (mm)	-
No. of compressors	1
Visual / acoustic alarm	Yes
Power failure alarm	Yes
Adjustable high/low temperature alarm	Yes
Open door alarm	Yes
Probe failure alarm	Yes
Alarm display as text - not codes	Yes
Contact for remote alarm	Yes
Prepared for GSM alarm module	Yes
Approx. hrs of battery back up for alarms and temperature display in the event of power cut	72 hours
Porthole for installation of PT100/CO <sub>2</sub> back up	No
Digital display	Yes
Data logger	Yes
RS 232 interface	Yes
RS 485 interface	Yes
USB up/down load	Yes
Defrost manual / auto	Yes
Castors	2 small in the back
Chart recorder	Yes
Drawers (pcs)	2
Adjustable drawers	2
Baskets (pcs)	No
Sub lids / doors (pcs)	No
Lighting	Yes
Lock	Yes
Inner liner material	Stainless steel
Cabinet material	Varnished steel
Colour (exterior)	White
Refrigerant	R134a

## Optional



**1** The GSM alarm module sends a SMS message to one or several coded telephone numbers in case the temperature exceeds a fixed range.



**2** SVS voltage stabilizers for excellent output voltage stability in case the voltage rises or drops.



CO<sub>2</sub>CARE



[www.arctiko.com](http://www.arctiko.com)

[www.co2care.eu](http://www.co2care.eu)