# matos. | Plus Eco 1365 S

#### ROLLEX MEDICAL NZ LTD

38E Highbrook Drive, East Tamaki, Auckland 2013, New Zealand PO Box 204159, Highbrook, Auckland 2161, New Zealand Phone: +64 9 274 0707 Fax: +64 9 274 0709 Email: sales@rollexmedical.co.nz www.rollexmedical.co.nz

# **Model Variations**

Eco 1365 S – Solid Door Eco 1365 S/G – Glass Door



The Matos<sup>®</sup> Plus Eco Cooled Incubators are a new range of purpose built Medical Chambers utilising patented technology. The cabinet and componentry have been specially designed for use in the Medical field.

## **Interior Finish**

All Matos<sup>®</sup> Plus Eco **Cooled Incubators** come with a high quality aluminium interior and use polyurethane foam thermal insulation. A stainless steel interior is also offered as an option.

## Lock Fitted as Standard

Maintains security and ensures the unit can only be opened by authorised personnel.

# Solid or Glass Door Options

Most models come with solid or glass door options enabling you to select the format which best suits your requirements.

# Auto Defrost

The advanced controller initializes a regular defrost sequence to decrease the chance of ice build-up while maintaining the temperature.

## **Energy Efficient**

Matos<sup>®</sup> Plus Eco **Cooled Incubators** are more energy efficient and kinder to the environment, meaning the running costs of the refrigerator are kept as low as possible.

#### **3 Year Extended Warranty**

When serviced by an approved service technician, the warranty is extended to 3 years.

Capacity	1365L	Power	550W
Dimensions External	1440w × 1990h × 860d	Air convection	Forced Air
Dimensions Internal	1310w x 1510h x 690d	Temperature range	+3°C - +40°C
Max shelf workload	30kg	Controller	Microprocessor with external LCD graphic display
Max unit workload	300kg	Interior	Aluminium (s/steel optional)
Door	Solid/Glass option	Housing	Powder coated sheet (s/steel optional)
Weight	195kg	Temperature resolution	0.1°C
Shelves fit/max	2x3/11	Temperature fluctuation at 4°C	+/- 0.5°C
Gas defrost	Optional	Voltage 50/60Hz	5/230∨
Refrigerant	R404A	Door Open Alarm	Yes
Refrigerant amount	0.27kg	Access Port	Yes
Castors	Yes	Internal light	Yes

## **Specifications**