

ROLLEX MEDICAL NZ LTD

38E Highbrook Drive, East Tamaki, Auckland 2013, New Zealand
 PO Box 204159, Highbrook, Auckland 2161, New Zealand
 Phone: +64 9 274 0707 Fax: +64 9 274 0709
 Email: sales@rollexmedical.co.nz www.rollexmedical.co.nz

Model Variations

Eco 200 R/DT – Solid Door, hot gas defrost
 Eco 200 R/GDT – Glass Door, hot gas defrost



MATOS Eco 200 R/DT

The Matos® Plus Eco fridge series is a new range of purpose built Medical and Vaccination Refrigerators utilising patented technology. The cabinet and componentry have been specially designed for use in the Medical field.

Interior Finish

All Matos® Plus Eco fridges come with a high quality aluminium interior and use polyurethane foam thermal insulation. A stainless steel interior is also offered as an option.

Lock Fitted as Standard

Maintains security and ensures the unit can only be opened by authorised personnel.

Solid or Glass Door Options

Most models come with solid or glass door options enabling you to select the format which best suits your requirements.

Auto Defrost

The advanced controller initializes a regular defrost sequence to decrease the chance of ice build-up while maintaining the temperature below 8°C. Matos® Plus Eco fridges are ordered with a gas defrost capability.

Energy Efficient

Matos® Plus Eco fridges are more energy efficient and kinder to the environment, meaning the running costs of the refrigerator are kept as low as possible.

3 Year Extended Warranty

When serviced by an approved service technician, the warranty is extended to 3 years.

Specifications

Capacity	200L	Power	170W
Dimensions External	620w x 1060h x 800d	Air convection	Forced Air
Dimensions Internal	520w x 860h x 420d	Temperature range	0°C – +10°C
Max shelf workload	10kg	Controller	Microprocessor with external LCD graphic display
Max unit workload	40kg	Interior	Aluminium (s/steel optional)
Door	Solid/Glass option	Housing	Powder coated sheet (s/steel optional)
Weight	52kg	Temperature resolution	0.1°C
Shelves fit/max	3/4	Temperature fluctuation at 4°C	+/- 0.5°C
Gas defrost	Optional	Voltage 50/60Hz	115/230V
Refrigerant	R1234	Internal light	Yes
Refrigerant amount	75 grams	Door Open Alarm	Yes
Castors	Optional	Access Port	Yes