

- ✓ **+2°C to +8°C Operating Temperature Range**
Conforms to MHRA guidelines.
- ✓ **Lock Fitted as Standard**
Maintains security and ensures the unit can only be opened by authorised personnel.
- ✓ **Solid or Glass Door Options**
Most models come with solid or glass door options enabling you to select the format which best suits your requirements.
- ✓ **Wire Shelves**
Enables optimum air flow inside the unit.
- ✓ **Unique Anti Microbial Handle**
Helps prevent the growth of bacteria and minimise the potential for cross contamination
- ✓ **3 Year Extended Warranty**
When serviced by an approved service technician, the warranty is extended to 3 years.
- ✓ **CCTC Certified**
CCTC and QCCP Approved. Exclusively endorsed by The Pharmacy Guild of Australia.



**The Pharmacy
Guild of Australia**



Specifications

Capacity	273L Gross / 269L Net	Power	1.08 kW/24h
Dimensions External	595w x 625d x 1565h	Internal Fan	Yes
Dimensions Internal	480w x 445d x 1382h	Temperature range	2°C – +8°C
Lock	Yes, 2 Keys	Controller	Digital, External
Door	Painted Aluminium/Glass	Interior	HIPS
Door Style	Right Hand Hinge Only	Housing	Powder coated sheet
Weight	68.5 kg	Voltage 50/60Hz	220-240V
Shelves fit/max	5	Internal light	Yes
Shelf Material	Wire	Door Open Alarm	Yes
Defrost	Auto	Access Port	No
Refrigerant	R600A	Noise Level (db)	<42db
Adjustable Feet (No & Position)	2 adjustable front feet, 2 rear rollers	Anti Microbial Handle	Yes
Country of Origin	United Kingdom	Colour	White / Green

ROLLEX MEDICAL NZ LTD

PO Box 204159, Highbrook, Auckland 2161, New Zealand
Phone: +64 9 274 0707 Fax: +64 9 274 0709
Email: sales@rollexmedical.co.nz www.rollexmedical.co.nz

ROLLEX MEDICAL (AUST) PTY LTD

PO Box 170 | Mt Kuring-gai 2080 | Sydney, NSW | Australia
Phone: 1300 880 441 | Fax: 1330 880 451
Email: sales@rollexmedical.com | www.rollexmedical.com.au